

Chapter Two - Triple Shower Thermostat with Double Volume Control -V6

Front View Dimensions:

- Overall width: 130
- Overall height: 305
- Recommended Max cut out: 120 x 55mm
- Labels: A, B, C, D

Side View Dimensions:

- Overall width: 169
- Overall height: 286
- Recommended Max cut out: 55mm
- Dimensions: 48, 51, 18, 85, 85
- Label: Ø38
- Label: *MIN 81 MAX 107
- Label: *Distance between back of Thermostat body & finished surface of wall

Legend:

- A** G3/4" COLD WATER INLET
- B** G3/4" HOT WATER INLET
- C** G3/4" WATER OUTLET
- D** G3/4" WATER OUTLET

Internal/External:

- INTERNAL
- EXTERNAL

Dimensions in mm. *Further installation instructions available as a downloadable PDF on the product page of our website.*



PRODUCT NAME

Studio/ **ORE**

**Chapter Two - Triple Shower Thermostat with
Double Volume Control -V6**

INTERNAL FIRST FIX: TM3HIP-V6

Min/Max Operating pressure: (bars)	0.5 - 6.0						
Flow rates: Bar/L per min Outlet 1	0.5/12.0	1.0/17.0	2.0/24.5	3.0/30.0	4.0/34.6	5.0/38.7	6.0/42.3
Flow rates: Bar/L per min Outlet 2	0.5/12.2	1.0/17.0	2.0/24.5	3.0/30.0	4.0/34.6	5.0/38.7	6.0/42.3
Connection:	3/4" BSP (NPT ADAPTERS ARE AVAILABLE)						

For specifications (in mm), please see reverse.

*Further installation instructions available as a downloadable PDF on the product page
of our website.*