


252
SC

Studio/ORE

PRODUCT NAME

Chapter Two - Dual Exposed Shower Thermostat with Two Ways Diverter, Single Curve



For Flow Rate information (Litres/min), please see reverse for details.

Dimensions in mm. Further installation instructions available as a downloadable PDF on the product page of our website.



Studio/ORE

PRODUCT NAME

Chapter Two - Dual Exposed Shower Thermostat with Two Ways Diverter, Single Curve


Min/Max Operating pressure: (bars)	0.5 - 6.0						
Flow rates: Bar/L per min (FIRST OUTLET)	0.5 / 13.0	1 / 18.5	2 / 27.2	3 / 33.7	4 / 38.5	5 / 42.9	6 / 46.0
Flow rates: Bar/L per min (SECOND OUTLET)	0.5 / 13.0	1 / 18.5	2 / 26.1	3 / 32.0	4 / 36.0	5 / 38.0	6 / 40.9
Connection:	1/2" BSP, 3/4" BSP (NPT ADAPTERS ARE INCLUDED)						

**Rose is NOT included with this product.*

* Rose Style Product Number Width

Minimalist, Victorian	G6M, G6V	6" (Ø150mm)
Minimalist, Victorian	G8M, G8V	8" (Ø200mm)
Minimalist, Flat	G10M, G10F	10" (Ø250mm)

G6, 8, 10 Minimalist



G6, 8, Victorian



G10 Flat



***Complimentary items include Products 74, 175 and 25-V2.*

For Specifications in mm, please see reverse for details.

Further installation instructions available as a downloadable PDF on the product page of our website.