


367
V4

PRODUCT NAME


Chapter Three - Wall Mounted Two Ways Diverter - V4

INTERNAL FIRST FIX: TM1HDIVIP-V5

**Min Max distances between
centre of outlet/inlet
& finished surface of wall*




- A:** G3/4" WATER INLET
- B:** G3/4" WATER OUTLET
- C:** G3/4" WATER OUTLET



Recommended Max cut out 55 mm

Back Plate Options:

- SQ / CR: 75 mm
- SQ / CR: 100 mm



*For flow rate information, min/max operating pressures (L/min)
& connection specifications, please see reverse for details.*

Dimensions in mm. Further installation instructions available as a downloadable PDF on the product page of our website.



PRODUCT NAME

Studio/ **ORE**

Chapter Three - Wall Mounted Two Ways Diverter - V4

INTERNAL FIRST FIX: TM1HDIVIP-V5

| | | | | | | | |
|---|--------------------------------------|----------|----------|----------|----------|-----------|-----------|
| Min/Max Operating pressure: (bars) | 0.5 - 6.0 | | | | | | |
| Flow rates: Bar/L per min (OUTLET 1) | 0.5 / 15.7 | 1 / 21.7 | 2 / 30.6 | 3 / 37.6 | 4 / 43.5 | 5 / 46.8 | 6 / 46.8 |
| Flow rates: Bar/L per min (OUTLET 2) | 0.5 / 15.7 | 1 / 21.8 | 2 / 30.2 | 3 / 37.2 | 4 / 43.0 | 5 / 46.81 | 6 / 46.81 |
| Connection: | 3/4" BSP (NPT ADAPTERS ARE INCLUDED) | | | | | | |
| Flow Restrictor: | N/A | | | | | | |

For Specifications in mm, please see reverse for details.

Further installation instructions available as a downloadable PDF on the product page of our website.