
05

18

Deck Mounted Basin/Bath Taps

Product shown will vary depending on model





Important information:

To ensure this product is installed properly you must read and follow these guidelines. The owner/user of this product must keep this information for future reference. This product must be installed by a professional licensed contractor. Only use a strap wrench or protected smooth jaw on any finished surface.



List of Parts:

Spout assembly (1 of each):

- Spout - Spout body and Fixing Thread - Flange - Spacer - Back Nut and Washer - Fixing kit

Side Valve (x2 of each)

- Body, Ceramic Disc Valve, Flange - Flange - Cylinder - Rubber washer - Back Nut

Flexible connection tubes (x4)

(2x Spout Connectors 2x Tap Connectors)

Handles (x2)

PLEASE NOTE: IT IS RECOMMENDED THAT THIS PRODUCT IS FITTED BY AN APPROVED PLUMBER/INSTALLER

1 Installation instructions

PLEASE REFER TO THE LIST OF PARTS AND DIAGRAM OVERLEAF

Prior to installation, please make sure the water supply is turned off.

1. If necessary plan out the 3 hole positions for the Spout and the two Side Valve bodies.

2. Fit the Spout to the Spout body and secure by tightening the Fixing Screw in the Spout body.

3. Fit the Flange to the Spout body Fixing Thread.

4. Fit the Spout assembly in the desired position on the base.

5. Hold the Spout assembly in position, fix the Washer (ensure flat is facing the overflow), Spacer and Back Nut in this sequence. Fully tighten the Nut.

6. Fit the Valve in position and screw on the Fixing Nuts and Washer.

7. Fully tighten the Back Nut.

8. Repeat actions 6 - 7, with the second Valve.

9. Attach the water feeds to the Valves.

10. Attach the Tap Connection Hoses to the Spout.

11. Turn on the water supply and check for water leaks. Allow to run for a few minutes to flush out any debris.

